



SIGGRAPH
ASIA2012

Embracing
the **digital**
convergence

CONFERENCE 28 Nov - 1 Dec
EXHIBITION 29 Nov - 1 Dec
Singapore EXPO



Foveated 3D Graphics

Brian Guenter Mark Finch Steven Drucker
Desney Tan John Snyder

Microsoft Research

Sponsored by ACM SIGGRAPH




High resolution image




Foveal vision: 2° - 5°



Acuity falloff with eccentricity e




Using Foveation



Sponsored by ACM SIGGRAPH




Human vision model




Human vision model

MAR
(Minimum
Angle of
Resolution)
degrees/cycle




Eccentricity
degrees

Human vision model



Human vision model



Related Work

- 2D Systems
 - Watson et al. 1997
 - Watson et al. 2004
- Lochsky & McConkie 2000
- Duchowsky 2007



Related Work

- 2D Systems
 - Watson et al. 1997
 - Watson et al. 2004
- Lochsky & McConkie 2000
- Duchowsky 2007



Related Work

- 2D Systems
 - Watson et al. 1997
 - Watson et al. 2004
- Lochsky & McConkie 2000
- Duchowsky 2007



Related Work


- 3D Rendering – Model based
 - Ohshima et al. 1996
 - Lubke et al. 2000
 - Reddy 2001
- 3D Rendering – Image based/hybrid
 - Levoy & Whitaker 1989
 - Murphy & Duchowski 2007



Related Work

3D Rendering


- Model based
 - Ohshima et al. 1996
 - Luebke et al. 2000
 - Reddy 2001



Related Work

3D Rendering


- Image based/hybrid
 - Levoy & Whitaker 1989
 - Murphy & Duchowski 2007




Related Work

3D Rendering



- Image based/hybrid
 - Levoy & Whittaker 1989
 - Murphy & Duchowski 2007





Foveated 3D Display




Foveated 3D Display



Foveated 3D Display



Foveated 3D Display



Foveated 3D Display




Challenges


- Latency
- Adaptable to general rendering
- Suitable for modern GPUs
- Aliasing
- Parameter selection




Latency




Latency




Latency




Latency




Latency




Latency




Latency



Latency





Latency




Latency

Tracker


10 ms



Latency



Latency



Latency

Tracker

10 ms

Render



16 ms

Scan out

8 ms



Pixel
switch

6 ms



Generality

Commodity hardware Gamer PC + eye tracker



Tobii TX300



2.67GHz CPU



120Hz
LCD

GTX 580 GPU

Generality

```
UpdateAll();
```

```
PushGlobalRenderState();
```

```
RenderAllObjects( currentCameraInfo );
```

```
PresentFrame();
```

Generality

UpdateAll();

PushGlobalRenderState();

```
foreach( layer in layers )
```

```
{
```

```
    layerCamInfo = PushLayer( currentCamInfo );
```

```
    RenderAllObjects( layerCamInfo );
```

```
    PopLayer();
```

```
}
```


```
CompositeLayers();
```

```
PresentFrame();
```

Aliasing



Aliasing




Anti-Aliasing Requirements


- Low impact on performance
- Not too blurry
- GPU friendly



Anti-aliasing




Temporal jitter



Anti-aliasing



Temporal Reverse Reprojection




**Previous
Frame**

**Current
Frame**

Anti-aliasing





Anti-aliasing





System parameters





Foveated 3D Display





Foveated 3D Display





Foveated 3D Display



Foveated 3D Display





Foveated 3D Display






Foveated 3D Display




ω_* = *native display acuity*






Pixel load per layer






Pixel load per layer





Pixel load per layer




Pixel load per layer




$$\frac{\text{Performance}}{\text{Quality}} \propto \text{MAR Slope}$$



$$\frac{\text{Performance}}{\text{Quality}} \propto \text{MAR Slope}$$



$$\frac{\text{Performance}}{\text{Quality}} \propto \text{MAR Slope}$$



User Study

- System Effectiveness




User Study

- System Effectiveness
- Validate Model
- Optimize Parameterization



Measuring Quality



0 0 9

TEST B

You will see a pair of fly-through animations.
There will be a short black screen between the first animation and the second.
You will vote on whether the first or second was higher quality.
Watch the animation carefully until prompted to vote.

Say "ready" when ready to begin:

A/B Comparison



0 0 7

TEST C

You will see an animated fly-through.
Every few seconds the settings will change.
Determine whether the quality was better at the beginning or end.
Watch the animation carefully until further instructions.

Say "ready" when you are ready to begin:




Ramp Test


Sponsored by ACM SIGGRAPH




User Study Results



User Study Results



Projected Performance Gains



Conclusions

- More pixels
- Cheap, robust eye tracking
- Higher visual quality
- Less hardware horsepower
- Lower power consumption



Thank you

Project page:

<http://research.microsoft.com/FoveatedDisplay>

Contact Mark Finch:

mafinch@microsoft.com





SIGGRAPH
ASIA 2012